

EC atitikties deklaracija

2011-05-24

UAB "Saint-Gobain statybos gaminiai"
Mėnulis 7
LT-04326 Vilnius
Lietuva

UAB "Saint-Gobain statybos gaminiai", įmonės kodas 111570853, adresas Mėnulis g. 7, LT-04326 Vilnius, tel: +370 5 2301 118 prisiimdami atsakomybę deklaruojame, kad

keramzito žvyras LWA 4/10 mm, R

pagamintas Saint-Gobain Ehitustooted AS, Haademeste 86001 Parnumaa, Estija susijęs su šia deklaracija atitinka visus standarto EN 13055-1 reikalavimus.

CE ženklavimo lydraščio kopija pridedama.

Atitikties deklaravimo pagrindas:

Gamintojo gamyklos Saint-Gobain Ehitustooted AS, Haademeste 86001 Parnumaa, Estija pateikta gaminio atitikties deklaracija.

Nortifikuotos įstaigos AS Teede Tehnokeskus išduotas sertifikatas 1073-CPD-G055-01



Įgaliotas UAB "Saint-Gobain statybos gaminiai" atstovas

Saugos ir žmogiškųjų išteklių vadovė



Ingrida Kemėšienė

* - tugevuse alampiir 95% tõenäosusega mis katab 90% materjalist

 05 1073- CPD – G055 - 01	 Saint-Gobain Ehitustooted AS Tehas Fibro ExClay 86001 Häädemeeste Pärnumaa, Eesti www.e-weber.ee		
	EN 13055-1 Lightweight aggregates for concrete, mortar and grout		
Product name: LWA 4/10 mm , R			
Article number: 150300			
Valid from: 01.09.2010			
Characteristic	Declared value		
Particle shape	Round, oblong		
Particle size	12,5 mm 11,2 mm 10 mm 8 mm 6,3 mm 4,0 mm	100 % 99 % 90 % 61% 32 % 15%	mm
Loose bulk density	300 (± 15%)		kg/ m ³
Percentage of crushed particles	10		%
Cleanliness	Not relevant		
Crushing resistance	Typical value Lower limit	1,3 0,64	N/mm ²
Chloride	NPD		% CL-
Acid-soluble sulphate	NPD		% SO ₃
Total sulphur	NPD		% S
Volume stability	NPD		
Water absorption	NPD		%
Emission of radioactivity	NPD, See third paragraph in ZA.3		
Release of heavy metals	NPD, See third paragraph in ZA.3		
Release of polyaromatic carbons	Not relevant		
Release of other dangerous substances	NPD, See third paragraph in ZA.3		
Durability against freeze/thaw	Durable according to long term experience		
Durability against alkali-silica reactivity	Not relevant		